

ASHLAND®		Page: 1
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0405602
Car Brite™ WORKOUT 2000™ Lotion Polish		Version: 1.0
CBOOA045-03		

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Car Brite™ WORKOUT 2000™
Lotion Polish

Recommended use of the chemical and restrictions on use

Details of the supplier of the safety data sheet Ashland P.O. Box 2219 Columbus, OH 43216 United States of America EHS Customer Requests@ashland.com	Emergency telephone number 1-800-ASHLAND (1-800-274-5263) Regulatory Information Number 1-800-325-3751 Product Information 614-790-3333
--	---

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3
 Skin irritation : Category 2
 Eye irritation : Category 2A
 Aspiration hazard : Category 1

GHS Label element

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : Flammable liquid and vapor.
 May be fatal if swallowed and enters airways.
 Causes skin irritation.
 Causes serious eye irritation.

Precautionary Statements : **Prevention:**
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

ASHLAND®		Page: 2
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0405602
Car Brite™ WORKOUT 2000™ Lotion Polish		Version: 1.0
CBOOA045-03		

Keep container tightly closed.
 Ground/bond container and receiving equipment.
 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Wash skin thoroughly after handling.
 Wear protective gloves/ eye protection/ face protection.

Response:

IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Do NOT induce vomiting.
 If skin irritation occurs: Get medical advice/ attention.
 If eye irritation persists: Get medical advice/ attention.
 Take off contaminated clothing and wash before reuse.
 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

Store in a well-ventilated place. Keep cool.
 Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
PETROLEUM DISTILLATES (STODDARD TYPE)	8052-41-3	Flam. Liq. 3; H226 Asp. Tox. 1; H304	10.90
HYDROTREATED HEAVY NAPHTHA	64742-48-9	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Eye Irrit. 2A; H319	8.25

SAFETY DATA SHEET

Revision Date: 05/22/2015

Print Date: 7/24/2015

SDS Number: R0405602

Car Brite™ WORKOUT 2000™ Lotion Polish

Version: 1.0

CBOOA045-03

		STOT SE 3; H335 Asp. Tox. 1; H304	
GLYCERIN	56-81-5	Not a hazardous substance or mixture.	4.07
WHITE MINERAL OIL	8042-47-5	Not a hazardous substance or mixture.	3.14
MORPHOLINE	110-91-8	Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 3; H331 Acute Tox. 3; H311 Skin Corr. 1A; H314 Eye Dam. 1; H318	1.50
PROPYLENE GLYCOL MONOPROPYL ETHER	1569-01-3	Flam. Liq. 3; H226 Eye Irrit. 2A; H319	1.12

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : Move to fresh air.
If breathed in, move person into fresh air.
If unconscious place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.

ASHLAND®		Page: 4
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0405602
Car Brite™ WORKOUT 2000™ Lotion Polish		Version: 1.0
CBOOA045-03		

Wash contaminated clothing before re-use.
If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.

If swallowed : Obtain medical attention.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.
Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material.
Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)
Cough
pain in the abdomen and lower back
Shortness of breath
irregular heartbeat
lung edema (fluid buildup in the lung tissue)
Difficulty in breathing
May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye irritation.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

ASHLAND®		Page: 5
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0405602
Car Brite™ WORKOUT 2000™ Lotion Polish		Version: 1.0
CBOOA045-03		

- circumstances and the surrounding environment.
Water spray
Foam
Alcohol-resistant foam
Carbon dioxide (CO2)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide
various hydrocarbons
Hydrocarbons
carbon
aluminum oxides
silicon oxides
Aldehydes
nitrogen oxides (NOx)
Hydrogen chloride gas
sulfur oxides
formaldehyde
nitrogen compounds
Ammonia
carbonyl fluoride
fluoride compounds
Hydrogen fluoride
toxic fumes
- Specific extinguishing methods :

Product is compatible with standard fire-fighting agents.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Remove all sources of ignition.
Use personal protective equipment.

ASHLAND®		Page: 6
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0405602
Car Brite™ WORKOUT 2000™ Lotion Polish		Version: 1.0
CBOOA045-03		

Ensure adequate ventilation.
 Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
 Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

- Environmental precautions : Prevent product from entering drains.
 Prevent further leakage or spillage if safe to do so.
 If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
- Other information : Comply with all applicable federal, state, and local regulations.
 Suppress (knock down) gases/vapours/mists with a water spray jet.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Open drum carefully as content may be under pressure.
 Avoid formation of aerosol.
 Provide sufficient air exchange and/or exhaust in work rooms.
 Do not breathe vapours/dust.
 Do not smoke.
 Container hazardous when empty.
 Take precautionary measures against static discharges.
 Avoid contact with skin and eyes.
 Smoking, eating and drinking should be prohibited in the application area.
 For personal protection see section 8.
 Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Observe label precautions.
 No smoking.
 Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

SAFETY DATA SHEET

Revision Date: 05/22/2015

Print Date: 7/24/2015

SDS Number: R0405602

Car Brite™ WORKOUT 2000™ Lotion Polish

Version: 1.0

CBOOA045-03

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
PETROLEUM DISTILLATES (STODDARD TYPE)	8052-41-3	TWA	100 ppm	ACGIH
		TWA	100 ppm	ACGIH
		REL	350 mg/m3	NIOSH/GUIDE
		REL	350 mg/m3	NIOSH/GUIDE
		Ceil_Time	1,800 mg/m3	NIOSH/GUIDE
		Ceil_Time	1,800 mg/m3	NIOSH/GUIDE
		PEL	500 ppm 2,900 mg/m3	OSHA_TRANS
HYDROTREATED HEAVY NAPHTHA	64742-48-9	TWA	100 ppm	SUPLR EXP
		GLYCERIN	56-81-5	PEL
		PEL	5 mg/m3 Respirable fraction.	OSHA_TRANS
WHITE MINERAL OIL	8042-47-5	REL	5 mg/m3 Mist.	NIOSH/GUIDE
		STEL	10 mg/m3 Mist.	NIOSH/GUIDE
		PEL	5 mg/m3 Mist.	OSHA_TRANS
		TWA	5 mg/m3 Mist.	TN OEL
		TWA	5 mg/m3 Inhalable fraction.	ACGIH
MORPHOLINE	110-91-8	TWA	20 ppm	ACGIH
		REL	20 ppm 70 mg/m3	NIOSH/GUIDE
		STEL	30 ppm 105 mg/m3	NIOSH/GUIDE
		PEL	20 ppm 70 mg/m3	OSHA_TRANS

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Hand protection

Remarks

: The suitability for a specific workplace should be discussed

ASHLAND®		Page: 8
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0405602
Car Brite™ WORKOUT 2000™ Lotion Polish		Version: 1.0
CBOOA045-03		

with the producers of the protective gloves.

- Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.
- Skin and body protection : Wear as appropriate:
 impervious clothing
 Safety shoes
 Flame-resistant clothing
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.
 Discard gloves that show tears, pinholes, or signs of wear.
 Wear resistant gloves (consult your safety equipment supplier).
- Hygiene measures : Wash hands before breaks and at the end of workday.
 When using do not eat or drink.
 When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state : liquid
- Colour : off-white
- Odour : like fruit
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : 32 °F / 0 °C
 No data available
- Boiling point/boiling range : > 149 °F / 65 °C
- Flash point : 122 °F / 50 °C
 Method: Pensky Martens closed cup
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit : No data available
- Lower explosion limit : No data available
- Vapour pressure : 23.3333333 hPa (20 °C)
 Calculated Vapor Pressure
- Relative vapour density : No data available

ASHLAND®		Page: 9
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0405602
Car Brite™ WORKOUT 2000™ Lotion Polish		Version: 1.0
CBOOA045-03		

Relative density : No data available

Density : +/- 0.005 0.968 g/cm3 (20 °C)

Solubility(ies)

Water solubility : partly soluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

excessive heat
Do not allow evaporation to dryness.
Exposure to sunlight.
Exposure to air or moisture over prolonged periods.

Incompatible materials : Acids
acrylates
Alcohols
Aldehydes
alkalis
glycols
halogenated hydrocarbons
Iron
isocyanates
Ketones
Metals
nitrites and other nitrosating agents
organic anhydrides
phenols

ASHLAND®		Page: 10
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0405602
Car Brite™ WORKOUT 2000™ Lotion Polish		Version: 1.0
CBOOA045-03		

reducing agents
steel
Strong bases
Strong oxidizing agents

Hazardous decomposition products

acrolein
Aldehydes
carbon dioxide and carbon monoxide
formaldehyde-like
Hydrocarbons
Hydrogen chloride gas
nitrogen compounds
Organic acids
toxic fumes
Ammonia
ketones
various hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Remarks: The thermal decomposition vapours of fluorinated polymers may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco.

Components:

PETROLEUM DISTILLATES (STODDARD TYPE):

Acute oral toxicity : LD 50 (Rat): > 5 g/kg

Acute dermal toxicity : LD 50 (Rabbit): > 3 g/kg

GLYCERIN:

Acute oral toxicity : LD 50 (Rat): 12,600 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC 50 (Rat): > 570 mg/m³
Exposure time: 1 h
Assessment: Not classified as acutely toxic by inhalation under GHS.

Acute dermal toxicity : LD 50 (Rabbit): > 10 g/kg

WHITE MINERAL OIL:

ASHLAND®		Page: 11
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0405602
Car Brite™ WORKOUT 2000™ Lotion Polish		Version: 1.0
CBOOA045-03		

Acute oral toxicity : LD 50 (Rat): 50,000 mg/kg

Acute dermal toxicity : LD 50 (Rabbit): > 2,000 mg/kg
Assessment: Not classified as acutely toxic by dermal absorption under GHS.

MORPHOLINE:

Acute oral toxicity : LD50 (Rat): ca. 1,900 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : Assessment: The component/mixture is classified as acute inhalation toxicity, category 3.

Acute dermal toxicity : LD 50 (Rabbit): ca. 500 mg/kg

PROPYLENE GLYCOL MONOPROPYL ETHER:

Acute oral toxicity : LD 50 (Rat, male): 4,330 mg/kg
Method: OECD Test Guideline 401

LD 50 (Rat, female): 2,490 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC 50 (Rat, male): > 1725 ppm
Exposure time: 4 h
Method: OECD Test Guideline 403
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD 50 (Rabbit, female): 4,330 mg/kg
Method: OECD Test Guideline 402

LD 50 (Rabbit, male): 3,775 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Causes skin irritation.

Product:

Result: Repeated exposure may cause skin dryness or cracking.

Remarks: May cause skin irritation and/or dermatitis.

Components:

PETROLEUM DISTILLATES (STODDARD TYPE):

Result: Mildly irritating to skin

HYDROTREATED HEAVY NAPHTHA:

Result: Irritating to skin

GLYCERIN:

Result: Not irritating to skin

WHITE MINERAL OIL:

Result: Not irritating to skin

ASHLAND®		Page: 12
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0405602
Car Brite™ WORKOUT 2000™ Lotion Polish		Version: 1.0
CBOOA045-03		

MORPHOLINE:

Result: Corrosive after 3 minutes or less of exposure

PROPYLENE GLYCOL MONOPROPYL ETHER:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Slightly irritating to skin

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:

PETROLEUM DISTILLATES (STODDARD TYPE):

Result: Mildly irritating to eyes

HYDROTREATED HEAVY NAPHTHA:

Result: Irritating to eyes

GLYCERIN:

Result: Mildly irritating to eyes

WHITE MINERAL OIL:

Result: Not irritating to eyes

MORPHOLINE:

Result: Corrosive to eyes

PROPYLENE GLYCOL MONOPROPYL ETHER:

Species: Rabbit

Result: Irritating to eyes

Method: OECD Test Guideline 405

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Components:

MORPHOLINE:

Genotoxicity in vitro

: Test Type: unscheduled DNA synthesis assay
 Test species: rat hepatocytes
 Metabolic activation: without metabolic activation
 Method: OECD Test Guideline 482
 Result: negative

: Test Type: In vitro mammalian cell gene mutation test
 Test species: mouse lymphoma cells
 Metabolic activation: without metabolic activation
 Method: OECD Test Guideline 476
 Result: positive

ASHLAND®		Page: 13
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0405602
Car Brite™ WORKOUT 2000™ Lotion Polish		Version: 1.0
CBOOA045-03		

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

Components:

HYDROTREATED HEAVY NAPHTHA:

Assessment: May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

May be fatal if swallowed and enters airways.

Components:

PETROLEUM DISTILLATES (STODDARD TYPE):

May be fatal if swallowed and enters airways.

HYDROTREATED HEAVY NAPHTHA:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Solvents may degrease the skin.

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

GLYCERIN:

Toxicity to fish : LC 50 (Goldfish (Carassius auratus)): > 5,000 mg/l
 Exposure time: 24 h
 Method: Static
 Remarks: Mortality

ASHLAND®		Page: 14
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0405602
Car Brite™ WORKOUT 2000™ Lotion Polish		Version: 1.0
CBOOA045-03		

Toxicity to daphnia and other aquatic invertebrates : LC 50 (Water flea (Daphnia magna)): > 10,000 mg/l
 Exposure time: 24 h
 Method: Static
 Remarks: Mortality

MORPHOLINE:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 380 mg/l
 Exposure time: 96 h
 Test Type: static test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Water flea (Daphnia magna)): 45 mg/l
 Exposure time: 48 h
 Method: OECD Test Guideline 202

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): 28 mg/l
 Exposure time: 96 h
 Test Type: static test

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Water flea (Daphnia magna)): 5 mg/l
 Exposure time: 21 d
 Test Type: semi-static test
 Method: OECD Test Guideline 211

PROPYLENE GLYCOL MONOPROPYL ETHER:

Toxicity to fish : LC 50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
 Exposure time: 96 h
 Test Type: static test

Toxicity to daphnia and other aquatic invertebrates : EC 50 (Water flea (Daphnia)): > 100 mg/l
 Exposure time: 48 h

Toxicity to algae : EC 50 (Green algae): 1,466 mg/l
 Exposure time: 96 h
 Test Type: Growth inhibition

Persistence and degradability

HYDROTREATED HEAVY NAPHTHA:

Biodegradability : Remarks: Not readily biodegradable.

MORPHOLINE:

Biodegradability : Result: Readily biodegradable
 Biodegradation: 92.6 %
 Exposure time: 22 d
 Method: OECD Test Guideline 301E

PROPYLENE GLYCOL MONOPROPYL ETHER:

Biodegradability : Biodegradation: 91.5 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301A
 Remarks: Readily biodegradable

ASHLAND		Page: 15
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0405602
Car Brite™ WORKOUT 2000™ Lotion Polish		Version: 1.0
CBOOA045-03		

Bioaccumulative potential

GLYCERIN:

Partition coefficient: n-octanol/water : log Pow: -1.76

MORPHOLINE:

Partition coefficient: n-octanol/water : log Pow: -0.86

PROPYLENE GLYCOL MONOPROPYL ETHER:

Partition coefficient: n-octanol/water : log Pow: 0.621

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

ASHLAND®		Page: 16
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0405602
Car Brite™ WORKOUT 2000™ Lotion Polish		Version: 1.0
CBOOA045-03		

U.S. DOT - ROAD

Not dangerous goods

U.S. DOT - RAIL

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TRANSPORT CANADA - ROAD

Not dangerous goods

TRANSPORT CANADA - RAIL

Not dangerous goods

TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

UN	1993	FLAMMABLE LIQUID, N.O.S. (PETROLEUM DISTILLATES)	3	III	LIMITED QUANTITY

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

UN	1993	Flammable liquid, n.o.s. (PETROLEUM DISTILLATES)	3	III	LIMITED QUANTITY

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

UN	1993	Flammable liquid, n.o.s. (PETROLEUM DISTILLATES)	3	III	LIMITED QUANTITY

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

UN	1993	LIQUIDO INFLAMABLE, N.E.P. (PETROLEUM DISTILLATES)	3	III	LIMITED QUANTITY

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no
------------------	----

ASHLAND®		Page: 17
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0405602
Car Brite™ WORKOUT 2000™ Lotion Polish		Version: 1.0
CBOOA045-03		

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Fire Hazard
Acute Health Hazard

SARA 313 Component(s)SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Pennsylvania Right To Know

WATER	7732-18-5	50.00 - 70.00 %
PETROLEUM DISTILLATES (STODDARD TYPE)	8052-41-3	10.00 - 20.00 %
HYDROTREATED HEAVY NAPHTHA	64742-48-9	5.00 - 10.00 %
ALUMINUM SILICATE CALCINED	66402-68-4	5.00 - 10.00 %
GLYCERIN	56-81-5	1.00 - 5.00 %
WHITE MINERAL OIL	8042-47-5	1.00 - 5.00 %
MORPHOLINE	110-91-8	1.00 - 5.00 %
ETHYLENE POLYMER	9002-84-0	1.00 - 5.00 %

New Jersey Right To Know

WATER	7732-18-5	50.00 - 70.00 %
PETROLEUM DISTILLATES (STODDARD TYPE)	8052-41-3	10.00 - 20.00 %
HYDROTREATED HEAVY NAPHTHA	64742-48-9	5.00 - 10.00 %
ALUMINUM SILICATE CALCINED	66402-68-4	5.00 - 10.00 %
GLYCERIN	56-81-5	1.00 - 5.00 %
WHITE MINERAL OIL	8042-47-5	1.00 - 5.00 %
MORPHOLINE	110-91-8	1.00 - 5.00 %

California Prop 65

WARNING! This product contains a chemical known to the State of California to cause cancer.

ASHLAND®		Page: 18
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0405602
Car Brite™ WORKOUT 2000™ Lotion Polish		Version: 1.0
CBOOA045-03		

QUARTZ / SAND 14808-60-7

BENZENE 71-43-2

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

ETHYLENE GLYCOL 109-86-4

MONOMETHYL ETHER

BENZENE 71-43-2

The components of this product are reported in the following inventories:

- TSCA : On TSCA Inventory
- DSL : All components of this product are on the Canadian DSL.
- AUSTR : On the inventory, or in compliance with the inventory
- NZIOC : Not in compliance with the inventory
- ENCS : On the inventory, or in compliance with the inventory
- KECL : On the inventory, or in compliance with the inventory
- PICCS : Not in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECL (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

ASHLAND®		Page: 19
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0405602
Car Brite™ WORKOUT 2000™ Lotion Polish		Version: 1.0
CBOOA045-03		

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 05/22/2015

NFPA:	HMIS III:						
<p style="text-align: center;">Flammability</p> <p style="text-align: center;">Special hazard.</p>	<table border="1"> <tr> <td style="background-color: blue; color: white;">HEALTH</td> <td style="text-align: center;">2</td> </tr> <tr> <td style="background-color: red; color: white;">FLAMMABILITY</td> <td style="text-align: center;">2</td> </tr> <tr> <td style="background-color: yellow; color: black;">PHYSICAL HAZARD</td> <td style="text-align: center;">0</td> </tr> </table> <p>0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	2	FLAMMABILITY	2	PHYSICAL HAZARD	0
HEALTH	2						
FLAMMABILITY	2						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification
Combustible Liquid Class II

Full text of H-Statements referred to under sections 2 and 3.

- H226 Flammable liquid and vapor.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H335 May cause respiratory irritation.

Sources of key data used to compile the Safety Data Sheet
Ashland internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ASHLAND®		Page: 20
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0405602
Car Brite™ WORKOUT 2000™ Lotion Polish		Version: 1.0
CBOOA045-03		

ACGIH : American Conference of Industrial Hygienists
 BEI : Biological Exposure Index
 CAS : Chemical Abstracts Service (Division of the American Chemical Society).
 CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
 FG : Food grade
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
 H-statement : Hazard Statement
 IATA : International Air Transport Association.
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
 IMDG : International Maritime Code for Dangerous Goods
 ISO : International Organization for Standardization
 logPow : octanol-water partition coefficient
 LCxx : Lethal Concentration, for xx percent of test population
 LDxx : Lethal Dose, for xx percent of test population.
 ICxx : Inhibitory Concentration for xx of a substance
 Ecxx : Effective Concentration of xx
 N.O.S.: Not Otherwise Specified
 OECD : Organization for Economic Co-operation and Development
 OEL : Occupational Exposure Limit
 P-Statement : Precautionary Statement
 PBT : Persistent , Bioaccumulative and Toxic
 PPE : Personal Protective Equipment
 STEL : Short-term exposure limit
 STOT : Specific Target Organ Toxicity
 TLV : Threshold Limit Value
 TWA : Time-weighted average
 vPvB : Very Persistent and Very Bioaccumulative
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
 DOT : Department of Transportation
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
 HMIRC : Hazardous Materials Information Review Commission
 HMIS : Hazardous Materials Identification System
 NFPA : National Fire Protection Association
 NIOSH : National Institute for Occupational Safety and Health
 OSHA : Occupational Safety and Health Administration
 PMRA : Health Canada Pest Management Regulatory Agency
 RTK : Right to Know
 WHMIS : Workplace Hazardous Materials Information System